



This machine is suitable for glass loading in insulating glass equipment, cleaning machine, edging machine and other equipment.
Servo motor control, simple operation, safety and reliability.

The operation is controlled by touch screen, and the picture is easy to understand.

It can meet the loading depth within 850mm, and can be loaded directly from the glass frame.

The machine has the functions of automatic alarm for material shortage, under-voltage waiting of sucker, power failure protection and so on, and the safety factor is extremely high.

High-quality vacuum sucker is used, with high negative pressure and sufficient suction, and the glass is firmly adsorbed and does not fall off.

The equipment has a unique lifting program device, which can effectively prevent glass damage caused by glass.

Can be customized according to customer needs.

WAL2540/3060

Automatic Glass Loading Machine

WAL2850
WAL3370

Custom sizes according to user's needs

	WAL2540	WAL3060
Power supply	AC220V 50HZ	AC220V 50HZ
Total power	5.5kW	11kW
Air pressure	0.6~0.8MPa	0.6~0.8MPa
Thickness of single glass	3~12mm	3~12mm
Max. grab glass size	2500×4000mm	3000×6000mm
Min. grab glass size	300×500mm	300×500mm
Transfer speed	2~48mm	2~48mm
Overall dimensions	4000×2800×3050mm	6200×2800×3550mm